

## **Brass Flow Indicator**

:SG-YL11-05 **Product Type** 

**Product Sizes** :DN15 to DN50(1/2"Inch to 2"Inch)

**Material of Construction** 

:SS304 / SS316 / SS316L or Brass Body&Cap

**Sealing O-Ring** :PTFE(White)/NBR(Black)/Viton(Black)

:Tempered Glass/Quartz Glass Sight Glass Impeller/Rotor :Plastic(Red)/PTFE(Red)

**Connection Way** :NPT,BSPP,BSPT Female Thread

Max. Working Temperature :100°C / 212°F for Plastic Impeller&NBR or NBR O-Ring

200°C / 392°F for PTFE Impeller&O-Ring

:0.6MPa / 6Bar / 87PSI(Up to 1.6MPa Customization) **Max. Operating Pressure** 

**Compatible Medium** :Water / Oil / Gas / Air / Liquids








Wenzhou Luosimeng Machinery Co.Ltd.

Email:sales@rosemoun.com.cn sales1@rosemoun.com.cn rosemounmachinery@hotmail.com







## Wenzhou Luosimeng Machinery Co.,Ltd.

(Sight Flow Indicator Manufacturer)

Tel.:+86-577-86896383 Fax:+86-577-86998170

Mobile:+86-13091902237 Factory:102nd&201st Room,19th Building,No. 696,5th Binhai Road,Economic and Technological Developme Zone Wenzhou, Zhejiang P.R.China