

Tubular Sight Flow Indicator

Product Type	:SG-YL11-057
Product Sizes	:DN6 to DN50(1/8" Inch to 2" Inch)
Material of Construction	
Body&Cap&Nut&Pole	:SS304 / SS316 / SS316L, Plastic, PPR
Sealing O-Ring	:PTFE(White)/NBR(Black)/Viton(Black)
Sight Glass	:Tempered Glass/Quartz Glass
Impeller/Rotor	:Plastic(Red)/PTFE(Red)
Connection Way	:NPT, BSPP, BSPT Female Thread
Max. Working Temperature	:100°C / 212°F for Plastic Impeller&NBR or NBR O-Ring 200°C / 392°F for PTFE Impeller&O-Ring
Max. Operating Pressure	:0.6MPa / 6Bar / 87PSI(Up to 1.6MPa Customization)
Compatible Medium	:Water / Oil / Gas / Air / Liquids

LSMSFI

Wenzhou Luosimeng Machinery Co.Ltd.

LSMSFI

Wenzhou Luosimeng Machinery Co.Ltd.

LSMSFI

Wenzhou Luosimeng Machinery Co.Ltd.

Wenzhou Luosimeng Machinery Co.,Ltd.
(Sight Flow Indicator Manufacturer)

Tel.: +86-577-86896383

Fax: +86-577-86998170

Mobile: +86-13091902237

Factory: 102nd & 201st Room, 19th Building, No. 696, 5th Binhai Road, Economic

Email: sales@rosemoon.com.cn sales1@rosemoon.com.cn rosemoonmachinery@hotmail.com

and Technological Development Zone Wenzhou, Zhejiang P.R.China

Web: www.rosemoon.com